

CONTRACTOR	
PROJECT	DATE
PREPARED BY	MODEL : PP32

## SERIES SPECIFICATIONS

PP32 Purple Primer is a special blend of fast acting solvents formulated to soften and swell PVC and CPVC Pipes and Fittings prior to cementing. The primer penetrates the surface of the pipe and the fitting to be joined and will provide a stronger joint. It is highly recommended that primer should be used on the installation of larger than 3" diameter pipes and fittings. Purple Primer may be used on all PVC and CPVC pipes and fittings, all sizes and all schedules.



## SPECIFICATIONS

Color:  
Purple

Storage Temp  
-10°F to 100°F

Specific Gravity  
6.578

Shelf life  
Unlimited (Unopened)

Low VOC  
Maximum VOC per SCAQMD  
1168/316A: 550 g/l

Application Temp  
-10°F to 110°F

## CERTIFICATIONS

This product is tested, certified and approved by the NSF International for use on potable (drinking) water drain, waste and vent system. It is also listed by the International Association of Plumbing & Mechanical Officials (IAPMO). It carries the Uniform Plumbing Code (UPC) seal. This cement meets ASTM Standard D 2564.

## ORDERING INFORMATION

Part Number: PP32

Case Dimensions (in.): 17x13x5.375

Case Quantity: 12 PCS

Item Weight (lbs.): 0.8

Case Weight (lbs.): 27

## UPC BARCODES

	GTIN-12	GTIN-14	IMS Code
PP32	190010302246	00190010302246	0268-0263



APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

CONTRACTOR	
PROJECT	DATE
PREPARED BY	MODEL : PP32

## SAFETY PRECAUTIONS

Ensure adequate ventilation to avoid vapor build up which may cause flash fire. Vapor build up may also cause dizziness, headaches or eye watering. If symptoms are experienced use respiratory protection (NOISH/MSHA TC 23 cor equivalent) or leave area and provide more fresh air. Avoid contact with eyes, skin and clothing by use of safety glasses and gloves. Professionals should consult ASTM Standard F 402-93 Safe Handling of Solvent Cements, Primers and Cleaners Used for Joining Thermoplastic Pipe and Fittings. Professional users should also read the Material Safety Data Sheet for the product.

**Inhalation:** If breathing is difficult vacate to fresh air. If breathing problems persist seek immediate medical attention.

**Eyes:** Flush eyes thoroughly with water for 15 minutes. Get immediate medical attention.

**Internal:** If swallowed give 1 or 2 glasses of water immediately, call physician, hospital or poison control immediately.

**DO NOT INDUCE VOMITING**

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION