

SPECIFICATION & FEATURES

Cata	log	Num	ber

Notes

RóHS

DIMENSIONS

Depth: 2-1/2"

Other Dimensions see below

Job/Title


CM-MSB MASONRY BOXES WITH DEVICE EARS 2-1/2" DEEP

DESCRIPTION:

Centaur's Masonry Boxes are used in the installation of electrical fittings and other devices in masonry walls. They are constructed from 16 gauge galvanized steel. These 2-1/2" deep, welded boxes with device ears include an FB bracket to directly mount on the flat side of a stud. Models range from 3 to 5 gang switch boxes.

CERTIFICATION:

UL file E227970, conforms to UL514A. acceptable for use in 2-hour fire rated walls.



FEATURES

Knockout:

CKO: Concentric K.O. (1/2" and 3/4" K.O.) Bracket:

FB: (L: 7-3/8", W: 1-9/16") Offset (9/16") Mounts on flat side of stud

CONFIGURATION DATA

Catalog No	No. of	Bracket &	Knockouts		WxH	Culp	Std.
	Gangs	Setback	Sides	Bottom	VVX⊓	Cu.ln.	Pkg.
CM-MSB-3-FB	3	FB, 9/16"	(8)-CKO	(3)-CKO	5-1/2″x3-3/4″	47.9	20
CM-MSB-4-FB	4	FB, 9/16"	(10)-CKO	(4)-CKO	7-3/8″x3-3/4″	63.6	20
CM-MSB-5-FB	5	FB, 9/16"	(12)-CKO	(5)-CKO	9-1/8″x3-3/4″	79.6	20

